

NOTES:

ELECTRICAL:



1. Current Rating: 1.5 Amps
2. Contact Resistance: $\leq 20 \text{ m}\Omega$ RRENT RATING
3. DC/AC Volt Endurance: DC1000V/AC750V 1min
4. Insulation Resistance: $\geq 500 \text{ M}\Omega$
5. TIA Cat.6 Perm.Link Test: Worst Pair NEXT Headroom $\geq 3.0\text{dB}$

ENVIRONMENTAL:

1. Operating temperature range : -10°C - $+60^{\circ}\text{C}$
2. Storage temperature range : -40°C - 70°C
3. Operating humidity range: 10%-90%

MECHANICAL:

1. Plastic parts: high quality engineering plastic
2. Housing: Zinc Die-Casting with high quality Nickel plating
3. PCB: FR-4, 1.2mm thickness
4. Jack Wire: 0.35 mm Phosphor bronze gold over nickel plating
5. IDC conductor: 0.5mm Phosphor bronze, tin-plating
6. Contact compatibility :accommodate 26 to 23 AWG solid
7. Plug Insertion Life ≥ 750 cycles
8. Durability : 200 termination cycles

 KAYBE® Right transmission for the future		Unit	mm	Client		Tolerances	
		REV		Weight			
		Scale		Material			
				Product NO:			
Designed by		BCAT6FTP180				.XX	±0.05
Verified by						Angle	±0.5°
Approved by		Description: CAT6 FTP – Tool Less Keystone 180°				First angle projection 	

Modification Career				
NO:	Modification	Modified by	Approved by	Date